



Elektrotechnik Karl-Heinz Mauz GmbH

GM48-500-5000-225-12.5D8 (Artikel-Nr. 860535)

EKULIT

SPECIFICATIONS:

Item	Unit	Specification
Rated voltage	VDC	6.0
Gear Ratio		1/225
Rotation		CW
Motor Position		All position in horizontal
Temperature	°C	0~30
Humidity	%	30~95
• Performance of Motor		
No-load Speed	rpm	5.200±10%
No-load Current	mA	60 (max.)
Stall Current	mA	1250 (max.)
Stall Torque	g.cm	60
• Performance of Gear motor		
Output Speed	rpm	22±10%
No-load Current	mA	100 (max.)
Stall Current	mA	1250 (max.)
Stall Torque	kg.cm	13.0
Rated Torque	g.cm	2000
Rated Current	mA	200 (max.)
Noise	dB	50
• The Dimension		
The Outside Shaft Length	mm	12.5
Shaft End Play	mm	0.05-0.50
Screw Size		3.5 mountinh hole
Dia of Shaft	mm	Ø5*D4.5mm

Adresse: Felix-Wankel-Str. 35 • 73760 Ostfildern/Nellingen

Tel: +49-711/3414023

Fax: +49-711/3414024

E-mail: info@ekulit.de Web site: www.EKULIT.de

GM48-500-5000-225-12.5D8 (Artikel-Nr. 860535)

EKULIT

DIMENSIONS :
(Unit: mm)

