

Features

- Height : 5.4mm.
- Load life : 85°C 2000 hours.



● SPECIFICATION

Item	Characteristic								
Operation Temperature Range	-40 ~ +85°C								
Rated Working Voltage	4 ~ 50VDC								
Capacitance Tolerance (120Hz 20°C)	±20%(M)								
Leakage Current (20°C)	I ≤ 0.01CV or 3 (μA) *Whichever is greater after 2 minutes						I : Leakage Current (μA)	C : Rated Capacitance (μF)	V : Working Voltage (V)
Surge Voltage (20°C)	W.V.	4	6.3	10	16	25	35	50	
	S.V.	5	8	13	20	32	44	63	
Dissipation Factor (tan δ) (120Hz 20°C)	W.V.	4	6.3	10	16	25	35	50	
	tan δ	0.35	0.26	0.20	0.16	0.14	0.12	0.12	
Low Temperature Stability	Impedance ratio at 120Hz								
	Rated Voltage (V)		4	6.3	10	16	25	35 ~ 50	
	-25°C / +20°C		7	4	3	2	2	2	
	-40°C / +20°C		15	8	6	4	4	3	
Load Life	After 2000 hours application of W.V. and +85°C ripple current value, the capacitor shall meet the following limits. (DC + ripple peak voltage ≤ rate working voltage)								
	Capacitance Change	≤ ±20% of initial value							
	Dissipation Factor	≤ 200% of initial specified value							
	Leakage current	≤ initial specified value							
Shelf Life	At +85°C, no voltage application after 1000 hours, the capacitor shall meet the limits for load life characteristics. (With voltage treatment)								
Resistance to Soldering Heat	Capacitors placed on a 250°C hot plate for 30 seconds with their electrode terminals facing downward will fulfill the following conditions after being cooled to room temperature.								
	Capacitance Change	≤ ±10% of initial value							
	Dissipation Factor	≤ initial specified value							
	Leakage current	≤ initial specified value							

● DIMENSIONS (mm)

D	L	A	H	I	W	P	K
4.0	5.4	4.3	5.5MAX	1.8	0.65±0.1	1.0	0.35 ^{+0.15} _{-0.20}
5.0	5.4	5.3	6.5MAX	2.2	0.65±0.1	1.5	0.35 ^{+0.15} _{-0.20}
6.3	5.4	6.6	7.8MAX	2.6	0.65±0.1	2.1	0.35 ^{+0.15} _{-0.20}



