



iMaXX ref.	Description
H1325	230 ± 10mm cable each side cable 1.5mm ² , thin wall insulation, black for use with F1500 normOTO series up to 20A
H1335	230 ± 10mm cable each side cable 2.5mm ² , thin wall insulation, red for use with F1500 normOTO series up to 30A

NOTES
Cover can be attached using tether to:
1. cable (prior to installation): slip ring around cable
2. fuse holder body: press ring over ball joint
Materials:
Body: PUR black, UL94-V0
Cover: Forprene black, UL94-V0
Contacts: Phosphor bronze, box type

F1500 series normOTO blade fuse reference table:

Rating [A]	Color	Volt [V]	iMaXX Reference
1	Black	32	F1501P
2	Gray	32	F1502P
3	Violet	32	F1503
4	Pink	32	F1504
5	Tan	32	F1505
7.5	Brown	32	F1575
10	Red	32	F1510
15	Blue	32	F1515
20	Yellow	32	F1520
25	Natural	32	F1525
30	Green	32	F1530
35	Dark green	32	F1535
40	Orange	32	F1540

Revisions			Drawn	Date	Appr.
a	10/05	re-designed body and contacts	Checked	10/02	GRH
b	08/07	re-drawn	Standards	12/13	BE
c	11/08	add cable length, tolerance	Approved	12/13	AdH
d	06/13	updated tables and notes			
e	12/13	updated dimensions	Scale 1 : 1		



F	Projection	Tolerance ± 0.2 mm unless otherwise noted	Title	H1325/H1335 series normOTO fuse holder
			Drawing type	schematic
			Drawing number	H1325/H1335 drawing 1
			Sheet	1 of 1
			Layers / Sheet	0 1 2 6 8 9 11 Sheet 01