

億力光電股份有限公司
EVERVISION ELECTRONICS CO., LTD.

Product Specification For LCD Module

(KVPF-7B-002-16)

Model NO. : VGG644824-6UFLWE(RoHS)






REVISION : 2

APPROVAL FOR SPECIFICATIONS ONLY

APPROVAL FOR SPECIFICATIONS AND SAMPLE

CUSTOMER :	APPROVED BY :
STD.	

EVERVISION LCM R&D CENTER

APPROVED BY	CHECKED BY	PREPARED BY	
	 		
DIRECTOR	MANAGER	Mechanism Engineer	Electronic Engineer

億力光電股份有限公司總公司
EVERVISION ELECTRONICS CO., LTD.
新北市中和區建一路 186 號 6 樓
6F., No.186, Jian 1st Rd., Zhonghe Dist.,
New Taipei City 235, Taiwan
TEL : +886 2 8227-2788
FAX : +886 2 8227-2799

億力光電股份有限公司台中分公司
EVERVISION ELECTRONICS CO., LTD.
-Taichung Branch
台中市潭子區建國路 19 號
No.19, Jianguo Rd., Tanzi Dist.,
Taichung City 427, Taiwan
TEL : +886 4 2532-8889
FAX : +886 4 2532-6689

勁佳光電(昆山)有限公司
VBEST ELECTRONICS(KUNSHAN) Co., Ltd.
江蘇省昆山市玉山鎮高科技工業園城北路 8 號
No.8, Chengbei Rd., Hi-Tech Industry Park,
Yushan Town, Kunshan City, Jiangsu, China.
TEL : +86 512 5778 7288
FAX : +86 512 5777 0688

勁佳光電(昆山)有限公司東莞分公司
VBEST ELECTRONICS(KUNSHAN)Co.,Ltd.
- DongGuan Branch
東莞市莞城區東縱大道天寶路 23 號
No.23 Tian Bao Rd., Dong Zong St.,
Dong Guan City, Guang Dong, China.
TEL : +86 769 3887 5000
FAX : +86 769 3896 0580

<http://www.evervisionlcd.com>

EVERVISION	MODEL NO.		PAGE
	VGG644824-6UFLWE	SPEC SAMPLE	2

1. Table of Contents

No.	Contents	Page
1	Table of Contents	2
2	Record of Revisions	3
3	Module Numbering System	4
4	Application	5
5	Features	5
6	General Specifications	5
7	Absolute Maximum Ratings	6
8	Electrical Characteristics	7
9	Block Diagram	8
10	Input / Output Terminals Pin Assignment	9
11	Interface Timing	12
12	Optical Characteristics	14
13	Reliability Test	17
14	Packaging	18
15	Precautions	19
16	Outline Drawing	21
17	Definition of Labels	22
18	Incoming Inspection Standards	24

3. Module Numbering System

V G G 6448 24 – 6 U F L W E

Serial No.:A~Z

Backlight Color:
N:Without Backlight;
A:Amber; **B:**Blue; **G:**Green;
L:Yellow; **O:**Orange; **R:**Red;
W:White; **Y:**YellowGreen;
X:Others

Backlight Type:
N:Without Backlight; **E:**EL; **F:**CCFL;
L:General LED; **H:**High NTSC LED ;
R:RGB LED; **X:**Others

LCD Model:
A:ASTN; **B:**STN Blue; **C:**CSTN; **D:**DSTN;
E:MSLC; **F:**TFT; **G:**STN Gray;
H:HTN ; **I:**IBN; **K:**Black Mask TN; **L:**LTPS; **M:**MVA;
N:Others; **O:**OLED; **P:**PLED; **S:**IPS;
T:TN; **U:**FSC TN; **W:**FSTN Black/White;
X:FFSTN; **Y:**STN Yellow

LCD Type:
R: Reflective/Positive;
S : Reflective/Negative ;
F : Transflective/Positive ;
G: Transflective/Negative ;
U: Transmissive/Positive ;
T: Transmissive/Negative ; **N:**Others

Temperature Range & View Direction:
 General Purpose : 1:6H 2:12H 3:3H 4:9H 5:Others
 High Performance: 6:6H 7:12H 8:3H 9:9H 0:Others

STD Product Serial No.: 01~99
 Customer Made Serial No.: A1,A2...A9,B1,B2...B9,C1..

Display Function:
 Segment Number / Characters Lines / Column and Row Dots
 / Length * Width of Other

Display Type:
C:Character Type; **G:**Graphic Type; **S:**Segment Type; **O:**Other

LCM Type:
B:COB; **F:**COF; **G:**COG; **H:**Heat Seal; **K:**Touch Key ; **S:**SMT; **T:**TAB; **O:**Others;

EVERVISION	MODEL NO.		PAGE
	VGG644824-6UFLWE	SPEC SAMPLE	5

4. Application

This specification is applied to the 5.7 inch VGA supported TFT-LCD module, and can display true 262,144 colors (6 bit/ color). This module is composed of a 5.7" TFT-LCD panel, a driver circuit and LED backlight unit.

5. Features

- VGA (640×480 pixels) resolution.
- Digital 18 bit parallel RGB.

6. General Specifications

Item	Specifications	Unit
Screen Size	5.7 (Diagonal)	inch
Display Format	640RGB(H)×480(V)	dot
Active Area	115.2(H)×86.4(V)	mm
Pixel Pitch	0.180(H)×0.180(V)	mm
Pixel Configuration	RGB Vertical Stripe	-
Display Mode	TN Type / Transmissive Mode / Normally White	-
Surface Treatment	Anti-Glare	-
Viewing Direction	6 O'clock (The Gray Inversion will appear at this direction)	-
Outline Dimension	144.0(W)×104.6(H)×13.0(D)	mm
Weight	(191)	g
RoHS Compliance	RoHS Compliance	-

7. Absolute Maximum Ratings

7.1 Absolute Ratings of Environment

Item	Symbol	Value		Unit	Note
		Min.	Max.		
Storage Temperature	T _{ST}	-30	+80	°C	(1)
Operating Temperature	T _{OP}	-20	+70	°C	(1)

Note1: Background color changes slightly depending on ambient temperature.

This phenomenon is reversible.

Note2: Please refer to item of RELIABILITY.

7.2 Electrical Absolute Ratings

7.2.1 TFT-LCD Module

(Ta=25±2°C, GND=V_{SS}=0V)

Item	Symbol	Value		Unit	Note
		Min.	Max.		
Power Supply Voltage	VDD	-0.3	4.0	V	-

7.2.2 Backlight Unit

(Ta=25±2°C)

Item	Symbol	Value		Unit	Note
		Min.	Max.		
Current of Backlight Unit	I _B	-	175	mA	(1)
Reverse voltage	V _R	-	15	V	(1)

Note (1) Permanent damage to the device may occur if maximum values are exceeded or reverse voltage is loaded.

8. Electrical Characteristics


8.1 TFT-LCD Module

(Ta=25±2°C)

Item	Symbol	Value			Unit	Note
		Min.	Typ.	Max.		
Power Supply Voltage	VDD	3.0	3.3	3.6	V	-
Power Supply Current	IDD	-	115	161	mA	(1)
Input High Threshold Voltage	VIH	0.7VDD	-	VDD	V	-
Input Low Threshold Voltage	VIL	0	-	0.3VDD	V	-
Power Consumption	P _L	-	395.5	553.7	W	(1)
Frame Frequency	F _V	-	60	-	Hz	-
Dot Clock	DCLK	-	25.175	-	MHz	-

Note (1) The specified power consumption is under the conditions at VDD=3.3V, F_V=60Hz, whereas a power dissipation check pattern below is displayed.

Black Pattern / 0 Gray



Active Area

8.2 Backlight Unit

(Ta=25±2°C)


Item	Symbol	Value			Unit	Note
		Min.	Typ.	Max.		
Current of Backlight Unit	I _B	-	140	-	mA	-
Voltage of Backlight Unit	V _B	-	(9.9)	-	V	I _B =140mA (2)
Power Consumption	P _{BL}	-	(1.39)	-	W	I _B =140mA
LED Life Time(25°C)	-	40000	50000	--	hr	(1) (2)

Note (1) : LED life time is defined as under 25±2°C , when the average brightness decrease to 50% of original brightness

Note (2) : The BLU is driven by constant current, the voltage value is for reference only.

9. Block Diagram

9.1 TFT-LCD Module with Backlight Unit



10. Input / Output Terminals Pin Assignment


10.1 TFT-LCD Module

Connector: CVILUX CF25331D0R0-05 or compatible connector

Pin No.	Symbol	I/O	Description
1	VSS	I	Ground
2	CLK	I	Clock signal
3	IHS	I	Horizontal synchronous signal
4	IVS	I	Vertical synchronous signal
5	VSS	I	Ground
6	R0	I	RED data (LSB)
7	R1	I	RED data
8	R2	I	RED data
9	R3	I	RED data
10	R4	I	RED data
11	R5	I	RED data(MSB)
12	VSS	I	Ground
13	G0	I	GREEN data(LSB)
14	G1	I	GREEN data
15	G2	I	GREEN data
16	G3	I	GREEN data
17	G4	I	GREEN data
18	G5	I	GREEN data(MSB)
19	VSS	I	Ground
20	B0	I	Blue data(LSB)
21	B1	I	Blue data
22	B2	I	Blue data
23	B3	I	Blue data
24	B4	I	Blue data
25	B5	I	Blue data(MSB)
26	VSS	I	Ground
27	DEN	I	Input data enable control
28	VDD	I	+3.3V power supply
29	VDD	I	+3.3V power supply

Pin No.	Symbol	I/O	Description
30	REV	I	Selection signal for horizontal/ vertical scanning direction. Note (1)
31	VSS	I	Ground
32	NC	I	No connection
33	VSS	I	Ground

Note (1)



10.2 Backlight Unit

Connector: JST BHSR-02VS-1(N) or compatible connector

Pin No.	Symbol	I/O	Description	Wire Color
1	VLEDA	I	Backlight LED Anode.	Red
2	VLEDC	I	Backlight LED Cathode.	Black

10.3 Color Data Input Assignment

The brightness of each primary color(red, green and blue) is based on the 6 bit gray scale data input for the color. The higher the binary input, the brighter the color. The table provides the assignment of color versus data input.

Color		Data Signal																	
		Red						Green						Blue					
		D05	D04	D03	D02	D01	D00	D15	D14	D13	D12	D11	D10	D25	D24	D23	D22	D21	D20
Basic Colors	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Green	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1
	Cyan	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1
	Magenta	1	1	1	1	1	1	0	0	0	0	0	0	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Gray Scale Of RED	Red(0) / Dark	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red(1)	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0
	Red(2)	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	Red(61)	1	1	1	1	0	1	0	0	0	0	0	0	0	0	0	0	0	0
	Red(62)	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red(63)	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
Gray Scale Of Green	Green(0) / Dark	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Green(1)	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0
	Green(2)	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	Green(61)	0	0	0	0	0	0	1	1	1	1	0	1	0	0	0	0	0	0
	Green(62)	0	0	0	0	0	0	1	1	1	1	1	0	0	0	0	0	0	0
	Green(63)	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
Gray Scale Of Blue	Blue(0) / Dark	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Blue(1)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
	Blue(2)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	Blue(61)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	0	1
	Blue(62)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	0
	Blue(63)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1

11. Interface Timing

11.1 Input Signal Characteristics


PARAMETER	Symbol	Min.	Typ.	Max.	Unit
HS setup time	T_{hst}	10	-	-	ns
HS hold time	T_{hhd}	10	-	-	ns
VS setup time	T_{vst}	10	-	-	ns
VS hold time	T_{vhd}	10	-	-	ns
Data setup time	T_{dsu}	10	-	-	ns
Data hold time	T_{dhd}	10	-	-	ns
DEN setup time	T_{esu}	10	-	-	ns
VS falling to HS falling time on odd field @ RGB mode	T_{HV_O}	-4	0	+4	T_{CPH}
VS falling to HS falling time on even field @ RGB mode	T_{HV_E}	0.4	0.5	0.6	T_H

PARAMETER	Symbol	Min.	Typ.	Max.	Unit
CLK frequency	F_{CPH}	-	25.175	-	MHz
CLK period	T_{CPH}	-	39.7	-	ns
CLK pulse duty	T_{CWH}	40	50	60	%
HS period	T_H	-	800	-	T_{CPH}
HS pulse width	T_{WH}	5	30	-	T_{CPH}
HS-DEN time	T_{HS}	112	144	175	T_{CPH}
DEN pulse width	T_{EP}	-	640	-	T_{CPH}
VS pulse width	T_{WV}	1	3	5	T_H
VS-DEN time	T_{STV}	-	35	-	T_H
VS period	T_V	-	525	-	T_H


Note: When SYNC mode is used, 1st data start from 144th CLK after HS falling (when $STHD[5:0]=00000$)

11.2 Waveform


11.2.1 Clock and Data input waveforms



11.2.2 Data input format for RGB Mode



11.2.3 The HS & VS timing of the ODD/EVEN field.




12. Optical Characteristics

The optical characteristics should be measured in a dark environment (≤ 1 lux) or equivalent state with the methods shown in Note (4).

Item		Symbol	Conditions	Min.	Typ.	Max.	Unit	Note
Contrast Ratio		CR	$\theta_x=0^\circ, \theta_y=0^\circ$ Viewing Normal Angle	200	(350)	-	-	(2)
Response Time		T_R		-	15	-	ms	(3)
		T_F		-	35	-	ms	
Luminance(Center)		Y		350	(450)	-	cd/m ²	(4)
Brightness uniformity		BUNI		80	(85)	-	%	(5)
Color Chromaticity	Red	R _x		0.565	0.615	0.665	-	(1),(4)
		R _y		0.302	0.352	0.402	-	
	Green	G _x		0.281	0.331	0.381	-	
		G _y		0.520	0.570	0.620	-	
	Blue	B _x		0.093	0.143	0.193	-	
		B _y	0.053	0.103	0.153	-		
	White	W _x	0.279	0.329	0.379	-		
		W _y	0.315	0.365	0.415	-		
Viewing Angle	Horizontal	θ_{x+}	CR \geq 10	55	(65)	-	deg.	
		θ_{x-}		55	(65)	-		
	Vertical	θ_{y+}		45	(55)	-		
		θ_{y-}		55	(65)	-		


Note (1) Definition of Viewing Angle (θ_x, θ_y):



Note (2) Definition of Contrast Ratio (CR):


$$\text{Contrast ratio (CR)} = \frac{\text{Luminance measured when LCD on the "White" state}}{\text{Luminance measured when LCD on the "Black" state}}$$

Note (3) Definition of Response Time (T_R, T_F):




Note (4) Measurement Set-Up:

The LCD module should be stabilized at a given temperature for 30 minutes to avoid abrupt temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting Backlight for 30 minutes in a windless room.



Note (5) Definition of brightness uniformity

$$\text{Brightness uniformity} = (\text{Min Luminance of 9 points}) / (\text{Max Luminance of 9 points}) \times 100\%$$



(單位 : mm)

EVERVISION	MODEL NO.		PAGE
	VGG644824-6UFLWE	SPEC SAMPLE	17

13. Reliability Test


No.	Test Items	Test Condition	Remark
1	High Temperature Storage Test	T _a = 80°C 240 hours	(1),(2),(3)
2	Low Temperature Storage Test	T _a = -30°C 240 hours	(1),(2),(3)
3	High Temperature Operation Test	T _a = 70°C 240 hours	(1),(2),(3)
4	Low Temperature Operation Test	T _a = -20°C 240 hours	(1),(2),(3)
5	High Temperature and High Humidity Operation Test	T _a =60°C 90%RH 240 hours	(2), (3)
6	Electro Static Discharge Test (non-operating)	-Panel Surface/Top Case : 150pF, 330Ω Air : ±15kV, Contact : ±8kV	(2)
7	Mechanical Shock Test (non-operating)	Half sine wave, 100G, 6ms 3 times shock of each six surfaces	(2)
8	Vibration Test (non-operating)	Sine wave : 10 ~ 55 ~ 10Hz amplitude : 1.5mm 3 axis, 2 hours/axis	(2)
9	Thermal Shock Test (non-operating)	-20°C (30min) ~ 70°C (30min) , 10 cycles	(2), (3)
10	Drop Test(with Carton)	Height : 80 _{cm} 1 corner, 3 edges, 6 surfaces	(2)

Note 1 : T_a is the ambient temperature of samples.


Note 2 : In the standard condition, there shall be no practical problem that may affect the display function.
After the reliability test, the product only guarantees operation, but don't guarantee all of the cosmetic specification.

Note 3 : Before cosmetic and function test, the product must have enough recovery time, at least 2 hours at room temperature.

14. Packaging



PARTS LIST					
	ITEM	SIZE(LxWxH) unit:mm	MATERIAL	Q.T.Y	NOTE
1	STATIC SHIEDING BAGS	300.0×145.0×0.09		60	
2	EPE PAD	345.0×30.0×20.0	EPE	8	
3	CARD BOARD	345.0×150.0×3.5	CARTON	6	
4	CARD BOARD	450.0×23.0×150.0	CARTON	16	
5	INTERNAL BOX	455.0×350.0×164.0	CARTON	2	
6	EXTERNAL BOX	475.0×370.0×375.0	CARTON	1	
7	PRODUCT	144.0×104.6×13.0		60	

	MODEL NO.		PAGE
	VGG644824-6UFLWE	SPEC SAMPLE	19

15. Precautions

15.1 Assembly and Handling Precautions


- (1) Do not apply rough force such as bending or twisting to the module during assembly.
- (2) It's recommended to assemble or to install a module into the user's system in clean working areas. The dust and oil may cause electrical short or worsen the polarizer.
- (3) Don't apply pressure or impulse to the module to prevent the damage of LCD panel and Backlight.
- (4) Always follow the correct power-on sequence when the LCD module is turned on. This can prevent the damage and latch-up of the CMOS LSI chips.
- (5) Do not plug in or pull out the I/F connector while the module is in operation.
- (6) Do not disassemble the module.
- (7) Use a soft dry cloth without chemicals for cleaning, because the surface of polarizer is very soft and easily scratched.
- (8) Moisture can easily penetrate into LCD module and may cause the damage during operation.
- (9) High temperature or humidity may deteriorate the performance of LCD module. Please store LCD module in the specified storage conditions.
- (10) When ambient temperature is lower than 10°C, the display quality might be reduced. For example, the response time will become slow.

15.2 Safety Precautions

- (1) If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth. In case of contact with hands, skin or clothes, it has to be washed away thoroughly with soap.
- (2) After the module's end of life, it is not harmful in case of normal operation and storage.

15.3 Terms of Warrant

- (1) Acceptance inspection period
The period is within one month after the arrival of contracted commodity at the buyer's factory site.
- (2) Applicable warrant period
The period is within twelve months since the date of shipping out under normal using and storage conditions.

	MODEL NO.		PAGE
	VGG644824-6UFLWE	SPEC SAMPLE	20

15.4 Caution


This Evervision LCD module has been specifically designed for use only in electronic devices in the areas of audio control, office automation, industrial control, home appliances, etc. The modules should not be used in applications where module failure could result in physical harm or loss of life, and Evervision expressly disclaims any and all liability relating in any way to the use of the module in such applications.

15.5 Precautions of Storage

If the displays are going to be stored for years, please be aware the following notices.


- (1) Please store the displays in a dark room to avoid any damages from sunlight and other sources of UV light.
- (2) The recommended long term storage temperature is between 10 ~35°C and <60% humidity to avoid causing bubbles between polarizer and LCD glasses, and polarizer peeling from LCD glasses.
- (3) It would be better to keep the displays in the container, which is shipped from Evervision, and do not unpack it.
- (4) Please do not stick any labels on the display surface for a long time, especially on the polarizer.

16.Outline Drawing



4	DRAWING	Chester	DATE	11/9/22	MODEL	VGG644824-6UFLWE
3	CHECK		DATE		TYPE	Assembly
2	APPROVE		DATE		PAGE	1 OF 1
1	INITIAL DRAWING	Chester	DATE	11/9/22	TOLERANCE:	.X ±0.5 .XX ±0.5 .X ±
REVISION	DESCRIPTION	REVISER	DATE		MATERIAL	Part Number
1			3	2		5
				4		6

EVERVISION
 億力光電股份有限公司



REV. 1 UNIT mm SCALE A4 SIZE (3)

Detail "A"
Scale: 40X

17. Definition of Labels


The bar code nameplate is pasted on each module as illustration, and its definitions are as following explanation.



(a) Module Name: VGG644824-6UFLWE

(b) Serial ID:

A B C D E F G H I J K L



Serial No.
 Factory Code
 Manufactured Date
 Screen Size

Serial ID includes the information as below :

- (a) Screen size (Diagonal) : Inch Code (ABCD)
 3.5" → 0350
 10.4" → 1040
- (b) Manufactured Date : Year, Month, Day (EFG)

Year (E)

Year	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009
Mark	0	1	2	3	4	5	6	7	8	9
Year	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019
Mark	A	B	C	D	E	F	G	H	I	J
Year	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029
Mark	K	L	M	N	O	P	Q	R	S	T
Year	2030	2031	2032	2033	2034	2035				
Mark	U	V	W	X	Y	Z				

Month (F)

Month	Jan.	Feb.	Mar.	Apr.	May	Jun.	Jul.	Aug.	Sep.	Oct.	Nov.	Dec.
Mark	1	2	3	4	5	6	7	8	9	A	B	C

Day (G)

Day	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Mark	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F	G
Day	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	
Mark	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	

(c) Factory Code (H) :

For EVERVISION internal use.

(d) Serial No. (IJKL) :


Manufacturing sequence of product, for example : 0001~9999.

18. Incoming Inspection Standards

18.1 The environmental condition of inspection

The environmental condition and visual inspection shall be conducted as below.

- (1) Ambient temperature $23 \pm 5^{\circ}\text{C}$
- (2) Humidity: $50 \pm 20\%$ RH
- (3) Viewing distance is approximately ≥ 30 cm
- (4) Viewing angle is normal to the LCD panel as Fig_1(45°)
- (5) Ambient Illumination: 800 ~1200 Lux for external appearance inspection



Fig_1



18.2. The defects classify of AQL as following:

- (1) Test method :According to ANSI/ASQC Z 1.4 .General Inspection Level II take a single time
- (2) The defects classify of AQL as following:

Class of defects	AQL	Definition
Major	0.65%	It is defect that is likely to result in failure or to reduce materially the usability of the intended function.
Minor	1.5%	It is a defect that will not result in functioning problem with deviation classified.

18.3 Inspection Parameters


Item	Specification/Description	Note
Display	No Display	-
	Malfunction	-
Operating	Contrast ratio	Out of Spec
	Line defect	No obvious Vertical and Horizontal line defect in bright , dark and colored.

Item		Specification/Description			Note	
Operating	Point Defect (red ,green ,blue ,dark, white)	Item	Acceptable number			Note: 1、4
			A	B	Total	
		BRIGHT DOT	0	2	2	
		DARK DOT	2	3	3	
		BRIGHT+DARK DOT	2	3	4	
		Two adjacent dot	0	1	1	
	Three or more adjacent dot	NOT ALLOWED				
	Tiny bright dot	Definition of Tiny bright dot : $\Phi < 1/2$ dot			Note: 3	
	Dense tiny highlights	ND 5% judgment $N \leq 5$ $N > 5$ Visually not allowed				
	MURA	Has the non-uniform phenomenon				
By 6% ND filter invisible						
					Note:4	


External Inspection (non-operating)	Line Shape · Scratch on the polarizer	L(mm)	W(mm)	Acceptable number	Note:2
		$L \leq 10$	$W \leq 0.1$	4	
		-	$W > 0.1$	0	
		$L > 10$	-	0	
	Dent or bubble on the polarizer	Dimension(mm)		Acceptable number	Note:3
		$D \leq 0.25$		Disregard	
		$D \leq 0.5$		4	
		$D > 0.5$		0	
	Fiber	L(mm)	W(mm)	Acceptable number	Note:6
		$L \leq 1.5$	$W \leq 1$	4	
		-	$W > 1$	0	
		$L > 1.5$	-	0	

Note1. The definition of dot defect : The dot defect was judged after repair and the size of a defective dot over 1/2 of whole dot is regarded as one defective dot.


Note2.




Note3. D : Diameter $D = (a+b)/2$



Note4. Bright dot is defined through 6% transmission ND Filter as following.




Note5.



Note6.

.Disregard if out of A.A.



	MODEL NO.		PAGE
	VGG644824-6UFLWE	SPEC SAMPLE	28

18.4 Handling of LCM

- (1) Don't give external shock.
- (2) Don't apply excessive force on the surface.
- (3) Liquid in LCD is hazardous substance. Must not lick and swallow. when the liquid is attach to your hand, skin, cloth etc. Wash it out thoroughly and immediately.
- (4) Don't operate it above the absolute maximum rating.
- (5) Don't disassemble the LCM.