

Wire connector with grease filling Set




Feature:


- Self-Stripping
- Moisture resistant
- Waterproof



2 wires























3 wires



4 wires

Package: 500pcs

Type	Product	Poles	Wire dia. (max.)	Conductor dia. (mm)	AWG	Insulation material	Working temperature	Rating (max.)	Color
2003C236		2 	1,52 mm	0,4 ~ 0,7	26-21	PC	0 ~ 90°C	50V/AC, 75V/DC	Yellow
2003C237		2 	2,08 mm	0,4 ~ 0,9	26-19	PP	0 ~ 65°C	50V/AC, 75V/DC	Orange
2003C238		3 	2,08 mm	0,4 ~ 0,9	26-19	PP	0 ~ 65°C	50V/AC, 75V/DC	Red
2003C239		4 	3,18 mm	0,9 ~ 1,3	19-16	PC	0 ~ 90°C	50V/AC, 75V/DC	Green
2003C240		4 	3,18 mm	0,5 ~ 0,9	24-19	PC	0 ~ 90°C	50V/AC, 75V/DC	Red
2003C241		2 	1,67 mm	0,4 ~ 0,9	26-19	PC	0 ~ 90°C	50V/AC, 75V/DC	Green
2003C242		4 	4,4 mm	0,9 ~ 1,3	19-16	PC	0 ~ 90°C	50V/AC, 75V/DC	Black
2003C243		4 	1,4 mm	0,4 ~ 0,7	26-21	PC	0 ~ 90°C	50V/AC, 75V/DC	Transparent
2003C244		4 	1,4 mm	0,4 ~ 0,7	26-21	PC	0 ~ 90°C	50V/AC, 75V/DC	Blue
2003C245		4 	1,4 mm	0,4 ~ 0,7	26-21	PC	0 ~ 90°C	50V/AC, 75V/DC	Green