



Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)  
 Contact Factory ([modshop@hammfg.com](mailto:modshop@hammfg.com)) for quotes  
 Solid models of this enclosure available in .stp or .x\_t  
 (Part number and text placement/orientation on our products are subject to change,  
 we do not recommend using them as a locating reference for modification purposes)

| NOTE  |                       |
|---|-----------------------|
| Purchased assembly includes box, lid, 2 cover screws.<br>Enclosure molded from general purpose ABS Plastic.<br>Other materials / colours available consult factory. |                       |
| Recommended Torque : (35-43) Ozf.in / (25-30) cN.m  |                       |
| PART NUMBERS  |                       |
| 1551TTFL Enclosure  |                       |
| Black Enclosure - Ral 9011 - UL94 - HB  | 1551TTFLBK            |
| Gray Enclosure - RAL 7035 - UL94 - HB   | 1551TTFLGY            |
| Translucent Blue - UL94 - HB  | 1551TTFLTBU           |
| ACCESSORIES   |                       |
| Black Cover Screws #4 X 1/2" Self-tapping   | 1591TS100BK (Pkg 100) |
| Plated Cover Screws #4 X 1/2" Self-tapping  | 1591TS100 (Pkg 100)   |
| P.C. Board Plastite Self Tapping Screw<br>[#2 x 3/16" self-tapping (4.8mm)]   | 1553WTS100 (Pkg 100)  |

Dimensions:  
mm  
[inches]

**HAMMOND  
MANUFACTURING®**

**1551TTFL**

[www.hammondmfg.com](http://www.hammondmfg.com)