


- NOTES:**
- MATERIALS:
 HOOD: PBT GF UL94 V-0 BLACK
 FRONTSEALING: SILICONE VMQ BLUE
 SCREW: STAINLESS STEEL
 O-RING: NBR BLACK
 - TEMPERATURE RANGE: -30°C TO +90°C
 - RECOMMENDED TORQUE FOR SCREW:
 35Ncm (3.1 in.LB)
 MAX. TORQUE: 68Ncm (6 in.LB)
 - SINGLE PACKED

* COMPLETELY TIGHTENED



Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm		scale:	1,5:1 (1:1)
	±0,3 unless otherw. specified				material:	SEE NOTES
	date	name		title:		
	drawn 07.02.2014	Heinrich		WATER RESISTANT D-SUB HOOD		
	appd. 07.02.2014	Huether		15 POS.		
	norm			SHORT SCREW 4-40UNC STAINLESS STEEL		
	d-old	15K1A1153		dwg no:		DIN-A3
	a	Origin		15K1A1436		sh: 1
	rev.	description	date	name	part no:	
					15-004720	

