

Tyco / Electronics
Raychem Circuit Protection
 308 Constitution Drive
 Menlo Park, CA 94025-1164
 Phone: 800-227-4856
 Fax: 800-227-4866

PolySwitch®
PTC Devices
 Overcurrent Protection Device

PRODUCT: miniSMDC014F

DOCUMENT: SCD 25113
 PCN: F67045
 REV LETTER: C
 REV DATE: MAY 6, 2003
 PAGE NO.: 1 OF 1

Specification Status: RELEASED

Maximum Electrical Rating

Voltage: 60V_{DC}
Current: 10A

Notes:

1. All terminations are tin plated.
2. Devices can be wave soldered.
3. Drawing not to scale

Marking:





TABLE I. DIMENSIONS:

	A		B		C		D	E
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MIN
mm:	4.37	4.73	0.635	0.890	3.07	3.41	0.25	0.20
in:	(0.172)	(0.186)	(0.025)	(0.035)	(0.121)	(0.134)	(0.010)	(0.008)

TABLE II. PERFORMANCE RATINGS:

CURRENT RATINGS**			TIME TO TRIP ** @ 1.5A	TIME TO TRIP ** @ 8.0A	RESISTANCE VALUES		POWER DISSIPATION
AMPERES AT - 40°C HOLD	AMPERES AT 20°C HOLD	AMPERES AT 60°C HOLD	SECONDS AT 20°C MAX	SECONDS AT 20°C MAX	OHMS AT 20°C MIN MAX*		WATTS AT 20°C MAX
0.23	0.140	0.090	0.150	0.008	1.50	6.00	0.75

* Maximum resistance is measured 1 hour after reflow.

** Values Specified were determined using PCB's with 0.030"X1.5 ounce copper traces.

Reference Documents: PS300, E. N. SMD1.0x

Precedence:

This specification takes precedence over documents referenced herein.

Effectivity:

Reference documents shall be the issue in effect on the date of invitation for bid.

CAUTION:

Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame.