

| | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | |
|---|-------------------|--|------------------|---|------------------------|---|-----------------------------|---------------|-----------------------------|
| A | 01 | CONTACT MATERIAL | PHOSPHOR BRONZE | | RECOMMENDED PCB LAYOUT | | FURTHER DOCUMENTATION | | |
| | 02 | CONTACT PLATING | TIN | | | | | | |
| | 03 | MATERIAL THICKNESS | 0.2MM | | | | | | |
| | 04 | APPLICABLE WIRE | AWG 20 TO AWG 24 | | | | | | |
| B | | | | | | | | | |
| C | | | | | | | FURTHER TESTING INFORMATION | | |
| D | TECHNICAL DRAWING | <p>Technical drawing showing front, side, and cross-sectional views of a female crimp terminal. Dimensions include: 1.12±0.10, 2.20±0.15, 11.00±0.25, 2.10±0.20, 6.80±0.20, 0.75±0.20, 0.20, 1.25±0.10, 2.50±0.25, 2.30±0.25, 1.95±0.25, and 2.00±0.25. Section lines A-A and B-B are indicated.</p> | | | RECOMMENDED PCB LAYOUT | | FURTHER DOCUMENTATION | ORDERING CODE | 87C30FC - SERIES NO. |
| E | | | | | | | | | R PACKING OPTION: R=REEL |
| F | | | | | | | | | 50 PLATING: 50=TIN |
| G | | | | | | | | | |
| H | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |

| | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|---|-----------|---------------|-------------|-------|--|-----------------|-------------------------------------|---|
| | REVISION: | TOPIC: | DATE: | NAME: | UNIT: | PART. NO.: | DESCRIPTION: | |
| | 1 | FIRST RELEASE | 12.Mar.2008 | 芮天娜 | MM | 87C30FC | FEMALE CRIMP TERMINAL FOR PITCH 3.0 | |
| | 2 | | | | | | | |
| | 3 | | | | | | | |
| | 4 | | | | | | | |
| 5 | | | | | | | | |
| | | | | | TOLERANCES (UNLESS OTHERWISE SPECIFIED): | | | |
| | | | | | n.X ±0.2 • n.nX ±0.15 | | | |
| | | | | | NO. OF PAGES: | COMPLIANT WITH: | GSN ELECTRONICS PTE LTD © | |
| | | | | | 1 of 1 | ROHS | HTTP://WWW.GSN.CN.COM | |