


ISOLATING TRANSFORMER

POWER : 14VA
 INPUT VOLTAGE : 2x115V
 FREQUENCY : 50/60Hz
 NOMINAL OUTPUT VOLTAGE : 2x24V

NON SHORT CIRCUIT PROOF TRANSFORMER
 IP00
 UL94HB
 OPERATING TEMPERATURE : -25°C to 50°C
 STORAGE TEMPERATURE : -25°C to 85°C
 INSULATION CLASS (IEC85) : B
 REQUIRED PROTECTION : ON PRIMARY 160mA (115V)
 80mA (230V)

STANDARDS :
 UL506 (File E111078)
 CSA 22-2 (File E111078)
 CE

CONFORM TO :
 EN61558-1
 EN61558-2-4



D					
C					
B					
A					
Rev	Date	Modification	Dessiné	Visa	

Finition:		Tolérance générale:	
Finition:		General tolerance:	
Ech: 1:1	Matière:		
	Material:		
Dessiné par: ROUSSEL.Ch	Date: 20/09/2005	Visa: J.P.M.	
DATA SHEET 45048			
UI 39x10.2			
		22 Allée du Clos des Charmes Z.A. Les Portes de la Forêt 77030 COLLEIGNY Tel : 01-60-37-55-55 Fax : 01-60-17-12-00	
		DS45048	