



UI 21/7.3

Dimensions without tolerances ± 0.3 mm, Soldering pin $\varnothing 0.6$,
Rights to make alterations and improvements hereby reserved

Frame size/Core height	Output ta 70 °C/B	Size (h)	Weight	Packaging unit
BV UI 21 / 7.3 mm	1.0 VA	14.9 mm	0.050 kg	40 pieces

- Capacity: 1.0 VA
- ta 70 °C/B meeting VDE 0570/
EN 61558 regulations/standard
- Circuit for 115 V
Bridge: 1 to 4 and 3 to 6
- Circuit for 230 V
Bridge: 3 to 4

- Secondary double voltage
Bridge: 8 to 11
- Secondary double current
Bridge: 7 to 11 and 8 to 12
- Test voltage: 6000 V

Order No.	Total output VA	Frame Size	Primary voltage V	Connecting pins prim.	Secondary voltage V	Current sec. mA	Connecting pins sec.	No-load voltage V
BV UI 21 0011	1.0	21	230	1-3	1 x 3	333	7-8	1 x 4.7
BV UI 21 0012	1.0	21	230	1-3	1 x 6	166	7-8	1 x 10.4
BV UI 21 0013	1.0	21	230	1-3	1 x 7.5	133	7-8	1 x 12.9
BV UI 21 0014	1.0	21	230	1-3	1 x 9	111	7-8	1 x 14.4
BV UI 21 0015	1.0	21	230	1-3	1 x 10	100	7-8	1 x 15.4
BV UI 21 0016	1.0	21	230	1-3	1 x 12	83	7-8	1 x 20.4
BV UI 21 0017	1.0	21	230	1-3	1 x 15	67	7-8	1 x 24.6
BV UI 21 0018	1.0	21	230	1-3	1 x 18	56	7-8	1 x 29.1
BV UI 21 0019	1.0	21	230	1-3	1 x 21	47	7-8	1 x 34.0
BV UI 21 0021	1.0	21	230	1-3	1 x 24	42	7-8	1 x 39.7
BV UI 21 0001	1.0	21	2 x 115	1-3/4-6	2 x 3	166	7-8/11-12	2 x 5.8
BV UI 21 0002	1.0	21	2 x 115	1-3/4-6	2 x 6	82	7-8/11-12	2 x 11.4
BV UI 21 0008	1.0	21	2 x 115	1-3/4-6	2 x 7.5	67	7-8/11-12	2 x 13.1
BV UI 21 0003	1.0	21	2 x 115	1-3/4-6	2 x 9	56	7-8/11-12	1 x 17.1
BV UI 21 0004	1.0	21	2 x 115	1-3/4-6	2 x 12	41	7-8/11-12	2 x 21.8
BV UI 21 0005	1.0	21	2 x 115	1-3/4-6	2 x 15	33	7-8/11-12	2 x 26.9
BV UI 21 0006	1.0	21	2 x 115	1-3/4-6	2 x 18	27	7-8/11-12	2 x 30.0
BV UI 21 0007	1.0	21	2 x 115	1-3/4-6	2 x 21	23	7-8/11-12	2 x 36.6

All these types are held on stock