



Dimensions without tolerances  $\pm 0.3$  mm,  
Rights to make alterations and improvements hereby reserved

Frame size/Core height	Output ta 70 °C/B	Size (h)	Weight	Packaging unit
BV 201 .... / 6 mm	0.35 VA	15 mm	0.025 kg	50/250 pieces*
BV 202 .... / 10 mm	0.50 VA	19 mm	0.035 kg	50/250 pieces*

\* It depends on kind of packaging

The BV 20 with Insulation class B properties is especially suitable for printed circuit boards, computer processors, other electronic applications, domestic appliances, telecommunications, lighting and photo technologies.

Particularly in regard to competitiveness on international markets and the product liability of manufacturers, the BV 20 offers users the greatest functional electrical safety and long-life service by reason of its superior quality for their products.

Order No.	Total output VA	Frame Size	Primary voltage V	Connecting pins prim.	Secondary voltage V	Current sec. mA	Connecting pins sec.	No-load voltage V
BV 201 0128	0.35	1	230	1-4	1 x 6	58	6-7	1 x 10.0
BV 201 0142	0.35	1	230	1-4	2 x 6	29	5-6/7-8	2 x 10.4
BV 201 0143	0.35	1	230	1-4	1 x 7.5	47	6-7	1 x 12.6
BV 201 0136	0.35	1	230	1-4	1 x 9	39	6-7	1 x 14.4
BV 201 0144	0.35	1	230	1-4	2 x 9	19	5-6/7-8	2 x 16.0
BV 201 0145	0.35	1	230	1-4	1 x 12	29	6-7	1 x 20.8
BV 201 0146	0.35	1	230	1-4	2 x 12	15	5-6/7-8	2 x 19.7
BV 201 0147	0.35	1	230	1-4	1 x 15	23	6-7	1 x 26.1
BV 201 0148	0.35	1	230	1-4	2 x 15	12	5-6/7-8	2 x 25.0
BV 201 0149	0.35	1	230	1-4	1 x 18	19	6-7	1 x 30.4
BV 201 0150	0.35	1	230	1-4	1 x 21	17	6-7	1 x 36.0
BV 201 0135	0.35	1	230	1-4	1 x 24	15	6-7	1 x 36.8
BV 202 0154	0.5	2	230	1-4	1 x 6	83	6-7	1 x 10.2
BV 202 0155	0.5	2	230	1-4	2 x 6	42	5-6/7-8	2 x 10.2
BV 202 0156	0.5	2	230	1-4	1 x 7.5	67	6-7	1 x 12.8
BV 202 0157	0.5	2	230	1-4	1 x 9	55	6-7	1 x 15.4
BV 202 0158	0.5	2	230	1-4	2 x 9	28	5-6/7-8	2 x 15.4
BV 202 0159	0.5	2	230	1-4	1 x 12	42	6-7	1 x 20.6
BV 202 0160	0.5	2	230	1-4	2 x 12	21	5-6/7-8	2 x 20.6
BV 202 0161	0.5	2	230	1-4	1 x 15	33	6-7	1 x 25.9
BV 202 0162	0.5	2	230	1-4	1 x 18	28	6-7	1 x 30.9
BV 202 0163	0.5	2	230	1-4	1 x 21	24	6-7	1 x 36.2
BV 202 0164	0.5	2	230	1-4	1 x 24	21	6-7	1 x 41.2

All these types are held on stock



Safety transformer

